



Lp.	Nazwa/typ konsoli	Y [mm]	X [mm]
1.	KONSOLA AGS HK-K1-S-3,5-235-250	235	250
2.	KONSOLA AGS HK-K1-S-3,5-255-270	255	270
3.	KONSOLA AGS HK-K1-S-3,5-275-290	275	290
4.	KONSOLA AGS HK-K1-S-3,5-295-310	295	310
5.	KONSOLA AGS HK-K1-S-3,5-315-330	315	330
6.	KONSOLA AGS HK-K2-S-7,0-235-250	235	250
7.	KONSOLA AGS HK-K2-S-7,0-255-270	255	270
8.	KONSOLA AGS HK-K2-S-7,0-275-290	275	290
9.	KONSOLA AGS HK-K2-S-7,0-295-310	295	310
10.	KONSOLA AGS HK-K2-S-7,0-315-330	315	330
11.	KONSOLA AGS HK-K3-S-10,5-235-250	235	250
12.	KONSOLA AGS HK-K3-S-10,5-255-270	255	270
13.	KONSOLA AGS HK-K3-S-10,5-275-290	275	290
14.	KONSOLA AGS HK-K3-S-10,5-295-310	295	310
15.	KONSOLA AGS HK-K3-S-10,5-315-330	315	330

MATERIAŁ :

NORMA	EN	AISI/ASTM	DIN
NAZWA	1.4301	304	X5CrNi18-10

TOLERANCJE WYKONANIA - klasa „v” wg. ISO 2768-1
 PRZEWODNOŚĆ CIEPLNA λ - 17 W/(mK)

Tytuł rys.	Skala:
KONSOLA AGS HK-S-Y-X	1:1
Nr rysunku:	Data rev.
[AGS HK]-S-Y-X	Rev. 00
	01.06.2017